

**Nylon 46 resin compsn. contg. boron nitride - useful for engineering plastics having good heat resistance and mechanical properties**

Patent Assignee: UNITIKA LTD (NIRA )

Number of Countries: 001 Number of Patents: 002

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 1121361	A	19890515	JP 87278499	A	19871104	198925 B
JP 2502631	B2	19960529	JP 87278499	A	19871104	199626

Priority Applications (No Type Date): JP 87278499 A 19871104

Patent Details:

Patent No	Kind	Lan	Pg	Main IPC	Filing Notes
JP 1121361	A		4		
JP 2502631	B2		3	C08L-077/06	Previous Publ. patent JP 1121361

Abstract (Basic): JP 1121361 A

Compsn. comprises 50-99wt.% nylon 46, and 1-50wt.% boron nitride.

The nylon 46 is made from adipic acid or its functional deriv., and tetramethylene diamine or its functional deriv. Pref. the boron nitride particles have an average particle size of 1-15 microns. The compsn. may be formed into powders, pellets, etc., and be moulded by pressure, injection, extrusion, etc.

USE/ADVANTAGE - For electric parts, motor car parts, etc. The moulding has good mechanical properties and heat resistance. Compared with such mouldings contg. glass, carbon, etc. fibre reinforcing materials or fillers of talc, mica, etc., the appearance (surface smoothness) and moulding-shrinkage are good.

(Dwg.0/0)

Title Terms: NYLON; RESIN; COMPOSITION; CONTAIN; BORON; NITRIDE; USEFUL; ENGINEERING; PLASTICS; HEAT; RESISTANCE; MECHANICAL; PROPERTIES

Derwent Class: A23; A85; L03

International Patent Class (Main): C08L-077/06

International Patent Class (Additional): C08K-003/38

File Segment: CPI

?